

What is claimed is:

1. A combination suitable for detecting damage in an object, said combination comprising fiber optic means and triboluminescent means each being adaptable to association with said object so that a mechanical event attendant said damage is capable of causing said triboluminescent means to emit light at least some of which is transmissible by said fiber optic means.

2. The combination according to claim 1, further comprising photosensitive means wherein, when at least some said emitted light is transmitted by said fiber optic means, said photosensitive means is capable of responding to said transmitted light so as to indicate the presence of at least some said transmitted light.

3. The combination according to claim 1, wherein:

said fiber optic means includes outer casing means and inner transmissive means;

at least a portion of said outer casing means is capable of allowing at least some said emitted light to pass therethrough so as to reach said inner transmissive means; and

said inner transmissive means is capable of transmitting at least some said emitted light which has passed through said outer casing means.

4. The combination according to claim 3, wherein:

said at least a portion of said outer casing means is at least two portions of said outer casing means; and

each said portion of said outer casing means is capable of allowing at least some said emitted light of a particular wavelength to pass therethrough; and

said particular wavelength differs for at least two said portions of said outer casing means.

5. The combination according to claim 1, wherein said fiber optic means includes open tip means, said open tip means being devoid of said outer casing means so as to allow at least some said emitted light to reach said inner transmissive means.

6. Damage-autosensitive apparatus comprising:

a structure;

at least one fiber optic line, each said fiber optic line being connectable to a photodetector and being situated so that a portion of said fiber optic line is in communication with said structure; and

at least one triboluminescent element, each said triboluminescent element being integrated with said structure and being sufficiently proximate a said fiber optic line so that, upon an occurrence of damage to said structure:

an accompanying mechanical action upon said triboluminescent element results in a luminescent emission of light by said triboluminescent element; and

at least a portion of said luminescently emitted light is transmissible to said photodetector via said fiber optic line.

7. Damage-autosensitive apparatus as recited in claim 6, wherein at least one fiber optic line is situated so that a portion of said fiber optic line is in communication with an external portion of said structure.

8. Damage-autosensitive apparatus as recited in claim 6, wherein at least one fiber optic line is situated so that a portion of said fiber optic line is in communication with an internal portion of said structure.

9. Damage-autosensitive apparatus as recited in claim 6, wherein at least one fiber optic line is situated so that a portion of said fiber optic line is at least one of the following:

in communication with an external portion of said structure;

in communication with an internal portion of said structure; and

in communication with both an external portion and an internal portion of said structure.

10. Damage-autosensitive apparatus as recited in claim 6, wherein:

said structure is an overall structure including a laminar composite structure having plural lamina; and

at least one said fiber optic line is situated so that a portion of said fiber optic line is positioned between two adjacent said lamina.

11. Damage-autosensitive apparatus as recited in claim 6, wherein:

said structure is an overall structure including a fiber-reinforced matrix composite structure having a matrix phase and plural fiber reinforcements situated in said matrix phase; and

at least one said fiber optic line is situated so that a portion of said fiber optic line is positioned within said matrix phase so as to function as a said fiber reinforcement.

12. Damage-autosensitive apparatus as recited in claim 6, wherein:

said structure is an overall structure including a matrix composite structure having a matrix phase and plural constituents situated in said matrix phase;

each said constituent is selected from the group consisting of fiber reinforcement, particle reinforcement and particle filler; and

at least some said triboluminescent elements are integrated with said matrix composite structure whereby each said triboluminescent element constitutes at least a part of a said constituent.

13. Damage-autosensitive apparatus as recited in claim 6, wherein said triboluminescent elements are integrated with said structure so that at least one of the following sets of conditions obtains:

(a) at least one said fiber optic line is situated so that a portion of said fiber optic line is in communication with an external portion of said structure, and at least some

said triboluminescent elements are sufficiently proximate said fiber optic portion communicating with said external structure portion;

(b) at least one said fiber optic line is situated so that a portion of said fiber optic line is in communication with an internal portion of said structure, and at least some said triboluminescent elements are sufficiently proximate said fiber optic portion communicating with said internal structure portion; and

(c) at least one said fiber optic line is situated so that a first portion of said fiber optic line is in communication with an external portion of said structure and so that a second portion of said fiber optic line is in communication with an internal portion of said structure, at least some said triboluminescent elements are sufficiently proximate said first fiber optic portion communicating with said external structure portion, and at least some said triboluminescent elements are sufficiently proximate said second fiber optic portion communicating with said internal structure portion.

14. Damage-autosensitive apparatus as recited in claim 6, wherein:

at least a section of each said fiber optic line portion communicating with said structure is permeable to light; and

at least a portion of said luminescently emitted light sufficiently permeates at least one said light-permeable section so that at least a portion of said permeated luminescently emitted light is transmissible to said photodetector.

15. Damage-autosensitive apparatus as recited in claim 14, wherein:

at least two sections of each said fiber optic line portion communicating with said structure are permeable to light;

each said light-permeable section is permeable to light characterized by a different wavelength.

16. Damage-autosensitive apparatus as recited in claim 14, wherein each said light-permeable section is one of:

a longitudinal section of the corresponding said fiber optic line portion; and

an end section of the corresponding said fiber optic line portion.

17. Damage-autosensitive apparatus as recited in claim 14, wherein said photodetector is producible of an indication of at least a portion of said transmitted permeated luminescently emitted light.

18. Damage-autosensitive apparatus as recited in claim 14, wherein:

each said fiber optic line includes an outer coaxial fiber optic portion and an inner coaxial fiber optic portion;

at least a portion of said luminescently emitted light is transmissible to said photodetector via said inner coaxial fiber optic portion; and

at least a portion of said luminescently emitted light sufficiently permeates said outer coaxial fiber optic portion of at least one said light-permeable section.

19. Damage-autosensitive apparatus as recited in claim 6, further comprising said photodetector, each said fiber optic line being connected to said photodetector, wherein, upon said occurrence of damage to said structure:

at least a portion of said luminescently emitted light is transmitted to said photodetector via said fiber optic line; and

said photodetector produces an indication of at least a portion of said transmitted permeated luminescently emitted light.

20. Damage-autosensitive apparatus as recited in claim 19, wherein:

each said fiber optic line includes an outer coaxial fiber optic portion and an inner coaxial fiber optic portion;

upon said occurrence of damage to said structure, at least a portion of said luminescently emitted light is transmitted to said photodetector via said inner coaxial fiber optic portion; and

at least a portion of said luminescently emitted light sufficiently permeates said outer coaxial fiber optic portion of at least one said light-permeable section.

21. A method for sensing mechanical damage, said method comprising:

triboluminescently radiating light in response to said damage; and

fiber optically conveying at least some said triboluminescently radiated light so as to be informative about said mechanical damage.

22. A method of sensing the damage condition of an object, said method comprising:

integrating triboluminescent material with said object; and

associating at least one fiber optic line with said object and with a photosensitive device so that, following a damage-causing event accompanied by a mechanical action upon at least some said integrated triboluminescent material, a quantity of a resultant triboluminescent light emanation is transmitted by at least one said fiber optic line to said photosensitive device.

23. A method as defined in claim 22, wherein following said damage-causing event accompanied by said mechanical action:

said quantity of said resultant triboluminescent light emanation is a second quantity of said resultant triboluminescent light emanation;

prior to said transmitting, a first quantity of said resultant triboluminescent light emanation is admitted by at least one said fiber optic line;

said resultant triboluminescent light emanation includes said first quantity of said resultant triboluminescent light emanation;

said first quantity of said resultant triboluminescent light emanation includes said second quantity of said resultant triboluminescent light emanation.

24. A method as defined in claim 23, said method further comprising providing at least one said fiber optic line, wherein:

said fiber optic line has an exterior membrane and an interior light-transmissive path; and

said exterior membrane is at least partially light-admissible along at least a portion of the length of said fiber optic line, said fiber optic line thereby being admissible of said first quantity of said resultant triboluminescent light.

25. A method as defined in claim 23, said method further comprising providing at least one said fiber optic line, wherein said fiber optic line is at least partially light-admissible at an extremity of said fiber optic line, said fiber optic line thereby being admissible of said first quantity of said resultant triboluminescent light.

26. A method as defined in claim 23, wherein at least one said fiber optic line is suitably distanced from said at least some triboluminescent material so as to be admissible of said first quantity of said resultant triboluminescent light.

27. A method as defined in claim 23, wherein following said damage-causing event accompanied by said mechanical action:

subsequent to said transmitting, a third quantity of said resultant triboluminescent light emanation is received by said fiber optic line; and

said second quantity of said resultant triboluminescent light emanation includes said third quantity of said resultant triboluminescent light emanation.

28. A method as defined in claim 27, wherein said associating of at least one said fiber optic line with said photosensitive device is performed so that said photosensitive device is capable of being indicative of said third quantity of said resultant triboluminescent light emanation.

29. A method as defined in claim 28, said method further comprising providing said photosensitive device, wherein said photosensitive device is capable of repeatedly receiving a said third quantity of a said resultant triboluminescent light emanation, said photosensitive device thereby being capable of monitoring said damage condition of said object.

30. A method as defined in claim 22, wherein at least one of the following obtains:

said integrating triboluminescent material with said object includes selecting at least one location at which said object is susceptible to damage; and

said associating of said at least one fiber optic line with said photosensitive device includes selecting at least one location at which said object is susceptible to damage.

31. A method as defined in claim 22, wherein:

said method further comprises providing at least one said fiber optic line;

said at least one fiber optic line includes at least two fiber optic line portions which are at least partially light-admissible;

each said fiber optic line portion is admissible only to light of a corresponding wavelength; and

at least two said corresponding wavelengths are different.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000